



EFFICIENTGRIP™

(Select sizes with ROF/ROF SoundComfort Technology®)
Original Equipment Tire on Select European Vehicles

FEATURES

- Optimized silica tread compound
- Wide Circumferential Grooves
- OE-tuned asymmetric tread design

BENEFITS

- Helps provide enhanced traction in wet conditions
- Help evacuate water from beneath the tread
- Provides responsive handling and a smooth touring ride



Dry Traction



Ultra Wet Traction



Steering Responsiveness



Original Equipment on Audi, BMW, Mercedes-Benz, Mini and Rolls-Royce

EFFICIENTGRIP SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/ MILE	UTQG	ORIGINAL EQUIPMENT FITMENT
205/55R16	91W	SL	BLT	112187381	225613	5.5 - 7.5	6.5	8.4	24.9	1,356	10	840	340 A A	Audi A3: 10, BMW 1 Series: 12-13
225/55R17	101V	XL	BLT	112032534	232872	6.0 - 8.0	7.0	9.2	26.8	1,819	10	781	340 A A	
* 235/45R18	94Y	SL	BLT	112028381	231870	7.5 - 9.0	8.0	9.3	26.3	1,477	10	794	320 A A	
* 235/50R18	99V	SL	BLT	112030381	232385	6.5 - 8.5	7.5	9.7	27.3	1,709	10	767	440 A A	
255/45R18	99Y	SL	BLT	112350381	218995	8.0 - 9.5	8.5	10.0	27.1	1,709	11	773	340 A A	Audi A7: 11-17
235/55R19	105V	XL	BLT	112019381	228640	6.5 - 8.5	7.5	9.7	29.2	2,039	11	717	440 A A	
EFFICIENTGRIP ROF														
205/55R16	91W	SL	BLT	112187344	222291	5.5 - 7.5	6.5	8.4	24.9	1,356	9	840	340 A A	BMW 1 Series: 14
* 225/45R18	91V	SL	BLT	112206344	217524	7.0 - 8.5	7.5	8.9	25.9	1,356	10	806	340 A A	BMW X1: 11-16 (F), Mini Countryman: 11-17
225/45R18	91W	SL	BLT	112303344	218705	7.0 - 8.5	7.5	8.9	25.9	1,356	10	806	340 A A	BMW X1: 12-16 (F)
225/45R18	91Y	SL	BLT	112005344	222729	7.0 - 8.5	7.5	8.9	25.9	1,356	10	806	340 A A	BMW 3 Series: 12-17 (F)
225/45R18	91V	SL	BLT	112031344	232663	7.0 - 8.5	7.5	8.9	25.9	1,356	10	805	340 A A	
255/40R18	95V	SL	BLT	112199344	217523	8.5 - 10.0	9.0	10.2	26.0	1,521	11	803	340 A A	BMW X1: 11-13 (R), BMW X1: 14-16
255/40R18	95Y	SL	BLT	112006344	222730	8.5 - 10.0	9.0	10.2	26.0	1,521	11	803	340 A A	BMW 3 Series: 12-17 (R)
235/45R19	95V	SL	BLT	112014344	227807	7.5 - 9.0	8.0	9.3	27.4	1,521	10	764	340 A A	Mercedes-Benz GLA: 15
255/40R19	100Y	XL	BLT	112228344	217692	8.5 - 10.0	9.0	10.2	27.0	1,764	10	773	340 A A	Audi A6: 11-14, A7: 11-17
255/50R19	103Y	SL	BLT	112068344	217245	7.0 - 9.0	8.0	10.4	29.1	1,929	11	718	340 A A	Rolls-Royce Ghost: 10-17 (R)
255/45R20	101Y	SL	BLT	112126344	217246	8.0 - 9.5	8.5	10.0	29.1	1,819	9	719	340 A A	Rolls-Royce Ghost: 10-17 (F)
285/40R20	104Y	SL	BLT	112185344	217239	9.5 - 11.0	10.0	11.4	29.0	1,984	11	721	340 A A	Rolls-Royce Ghost: 10-17 (R)
EFFICIENTGRIP ROF SCT (SOUNDCOMFORT TECHNOLOGY)														
245/45R19	102Y	XL	BLT	112020391	230247	7.5 - 9.0	8.0	9.6	27.7	1,874	9	755	340 A A	
275/40R19	101Y	SL	BLT	112026391	230248	9.0 - 11.0	9.5	10.9	27.7	1,819	10	755	340 A A	

*Discontinued 2016.

ROF, RunOnFlat® radial. Refer to the RunOnFlat owner's manual/limited warranty recommendations on operation at low or no air pressure. Pressure monitoring system required. Sold separately. Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.

EFFICIENTGRIP™ PERFORMANCE ROF

EFFICIENTGRIP PERFORMANCE ROF SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32NDS)	REVS/ MILE	UTQG	ORIGINAL EQUIPMENT FITMENT
195/55R16	87W	SL	BLT	112015379	228037	5.5 - 7.0	6.0	7.9	24.4	1,201	10	856	340 A A	Mini Cooper F56: 14-15

ROF, RunOnFlat® radial. Refer to the RunOnFlat owner's manual/limited warranty recommendations on operation at low or no air pressure. Pressure monitoring system required. Sold separately. Do not attempt to mount 16" rim diameter tires on 16.5" rim diameter wheels; this may result in serious injury or death.