Logstomper FX23 STF HF-4







Segmentation of Forestry at ATA





Forestry tires has different operational needs



Agriculture operations





- Mostly even surface
- Soil protection & environment friendly
- Traction, Self cleaning & Low soil compaction
- On/Off road suitability
- Increased productivity

Forestry operations



- Mostly uneven surface Hill side
- Traction
- Stability
- Cuts & Puncture resistance
- Suitable to operate with ancillary aids
- Self cleaning & low soil compaction







- Stability
- Low down time
- Low heat built up
- Low wear
- Higher load carrying



Forestry operations are much tougher hence need toughest tires



Various activities are carried out in forestry operations and different types of applications are used for the same-

 A skidder is any type of heavy vehicle used in a logging operation for pulling cut trees out of a forest in a process called "skidding", in which the logs are transported from the cutting site to a landing.







Key Operational Needs of Skidder tire

Parameters

- Superior traction
- High puncture resistance
- Suitable for heavy duty application
- Self cleaning
- Cut and crack resistance
- Low slippage
- Side and longitudinal stability
- Suitable to be used by chains

Chains are used in this tires as ancillary traction aids.



Why **How** What

Expectations from the tire	Solution	
Superior traction	Variable lug angle	
Self cleaning	Plateau layers	
Cut and crack resistance	Forestry compound	
Side and longitudinal stability	Variable lug angle	
High puncture resistance	Steel belt construction	



Logstomper FX23 STF HF-4















Features-

- Large ground contact area provides wide footprint.
- Special lug design
- Less damage to soil
- Gives good self-cleaning
- Provides excellent traction
- Slide-slippage proof

Special compound + Steel Belted construction

Protects against cuts & puncture

Centre Overlapping

- This provides good roadability
- Drive comfort

Designed for all temperatures, and it performs well in "downed" timber

Application







Logstomper FX23 STF HF-4







SKU Range -

RIM	SIZE	PR
32	78x45.00-32	20