

Product Data

Axle Limited Slip 80W-90

GL-5 Limited Slip Gear Oil

Description

Castrol Axle Limited Slip 80W-90 gear oil is a multi-grade GL-5 gear lubricant.

Application

Castrol Axle Limited Slip 80W-90 is a multi-grade GL-5 gear lubricant that provides excellent performance in passenger cars and light truck rear wheel drive and four wheel drive axles.

Advantages

- Recommended for service fill of all limited slip differentials in passenger cars and Light trucks calling for SAE 80W-90 and API Service GL-5 specifications.
- Recommended for applications calling for Ford ESP-M2C154-A and GM 9985290.
- Recommended for service fill of conventional and limited slip differentials calling for an API Service GL-5, SAE 80W-90 gear oil.

Typical Characteristics

Name	Method	Units
Kinematic Viscosity at 100°C	ASTM D445	cSt
Kinematic Viscosity at 40°C	ASTM D445	cSt
Viscosity Index	ASTM D 2270	
Brookfield Viscosity at -26°C	ASTM D-2983	cSt
Pour Point	ASTM D97 °	°C (°F) max.
Flash Point COC	ASTM D92	°C (°F) max.
Specific Gravity at 15°C (60°F)	ASTM D1298	grams/ml
API Gravity	ASTM D287	Pounds Per Gallon

Additional Information

Product Performance Claims

API GL-5 Service fill limited slip

Axle Limited Slip 80W-90 05 Sep 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2

Plant Office:3660 Lakeshore Blvd West , Toronto, ON M8W 1P2 -

Phone 1-800-268-5339 Fax 416-252-7315 Plant Office telephone: 1 800 268-5339 Trade: 1 888 CASTROL Consumer: 1 800 CASTROL Technical Inquiries: 1 800 462-0835

E-mail info@wakefieldcanada.ca Website www.wakefieldcanada.ca www.castrol.com

Page: 2/2