



Castrol HD Motor Oil 50

Monograde Motor Oil

Description

Castrol HD Motor Oil 50 is a premium monograde oil engineered for greater protection against thermal breakdown

Application

Castrol Motor Oil HD 50 is suitable for use in vehicles where the manufacturer recommends an API SP or earlier specification SAE 50 Monograde lubricant.

Advantages

Castrol HD Motor Oil 50 :

- Provides maximum wear protection in warm climates.
- Use HD 50 when ambient temperature is above 60°F/ 15°C.

Typical Characteristics

Name	Method	Units	Castrol HD Motor Oil 50
Density @ 15C, Relative	ASTM D4052	g/ml	0.881
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.3
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	167
Viscosity Index	ASTM D2270	None	113
Pour Point	ASTM D97	°C	-22
Flash Point, PMCC	ASTM D93	°C	263
Total Base Number, TBN	ASTM D2896	mg KOH/g	6.9

Product Performance Claims

API SP

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol HD Motor Oil 50

24 Dec 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com